


SPECIFICATIONS

Classification:	ASTM F1700 Class III Type B
Total Thickness:	0.120" (3.0 mm)
Wear Layer Thickness:	32 mil (0.8 mm)
Edge Treatment:	Square (SE) or Slight Bevel (SB)
Emboss:	Pathway (PH)
Warranty:	20-Year Limited Commercial Wear Warranty
Colors:	44
Adhesive:	Tarkett RollSmart™, CENTI 2001 Wet Set, CENTI 6000 SP, CENTI 2000 EP or other approved adhesives.

Installation Methods:



Products shown: ICA 334C & 329C

SIZE	6" x 36" (15.24 cm x 91.44 cm)
	18" x 36" (15.24 cm x 91.44 cm)

TESTING

Flexibility:	ASTM F137	Passes
Dimensional Stability:	ASTM F2199	Passes
Static Load:	ASTM F970	Passes
Residual Indentation:	ASTM F1914	Excellent
Flammability:	ASTM E648	CRF≥0.45 watts/cm² NFPA Class 1
Slip Resistance:	ASTM D2047	Passes >0.5 ADA Compliant
Smoke Density:	ASTM E662	Passes <450 D ^{MC}
Resistance to Light:	ASTM F1515	Excellent
Chemical Resistance:	ASTM F925	Excellent
Resistance to Heat:	ASTM F1514	Excellent

ENVIRONMENTAL DATA

Recycled Content:	27.5% Preconsumer	
Materials:	No Heavy Metals; Non-Toluene Ink System	
Indoor Air Quality:	Meets CDPH Standard Method v1.1-2010; FloorScore® Certification	
Recyclability:	100% Recyclable through our ReStart® Program	
LEED Scoreboard:	LEED 2009	LEED v4
	MRC2 Construction Waste Management	MRC2 Building Product Disclosure and Optimization – Environmental Product Declarations
	MRc4 Recycled Content	MRc3 Building Product Disclosure and Optimization – Sourcing of Raw Materials
	MRc5 Regional Materials	MRc5 Construction and Demolition Waste Management
	IEQ 4.1 Low-Emitting Adhesives	IEQc2 Low-Emitting Materials
	IEQ 4.3 Low-Emitting Materials Flooring	
Manufacturing:	Made in the USA ISO 9001 Quality Management System ISO 14001 Environmental Management System OHSAS 18001 Occupational Health and Safety Management System	

Packaging: Packaged in recycled, corrugated cardboard



- For samples, warranties and more information, visit <http://collectionsinfinies.tarketta.com/>.
- Specifications are subject to nominal manufacturing variances. Material supply and/or manufacturing processes may necessitate changes without notice.
- Chair glides are recommended for optimum textural performance. Absent the use of chair glides, more intensive maintenance will be required for areas in direct contact with furniture footing, and some degree of appearance change is to be expected.